

AKRON ANTICONGELANTE 50/50



PRODUCT DESCRIPTION

Akron Anticongelante 50/50 is formulated with Ethylene Glycol and additive system to protect the cooling system automotive engine against metal corrosion, including aluminum. Meets ASTM 3306 and D 4985, SAE J-1034 specification. It's HOAT (Hibryd Organic Acid Tecnology).

BENEFITS

- Maximum protection under low and high temperatures.
- Ready to use.
- Excellent metal corrosion protection, including aluminum.
- Reduce pour point.
- Fast and excellent air separation.
- Good protection against rust in ferrous metallic surfaces.
- Low tendency foam formation.
- No attack hose elastomers.
- Compatible with HOAT & OAT Coolants.
- Nitrates, Silicates and Fosfates free.

APPLICATIONS

Akron Anticongelante 50/50 recommended for all gasoline and diesel engines. Can be used in industrial applications where the owners manual requires HOAT coolants.

TYPICAL INSPECTIONS

PROPERTY	ASTM METHOD	RESULTS
Product Code		1042
Appearance		Clear & Brilliant
Color		Yellow
Density, g/ml	D 1122	1.075
pH	D1287	10.5
Alkaline Reserve, mg KOH/g	D 1121	8.0
Boiling Point, °C	D 1120	108
Pour Point, °C	D 1177	-37
Corrosion Test	D 1384	Pass
Ash Content, %wt	D 1119	1.2
Water Content, %	D 123	50

